


ZOWER 中沃

www.firesafetydoor.com



RELIABLE
OEM & ODM
PROFESSIONAL

ZOWER 中沃 Protect Safety
& Security



STEEL FIRE DOOR



01	COMPANY INFORMATION	2
02	STEEL FIRE DOOR	6
	DOUBLE STEEL FIRE DOOR	6
	SINGLE STEEL FIRE DOOR	14
	TECHNICAL INTRODUCTION	22
	DOOR SURFACE TREATMENT	30
	SPRAYING PROCESS COLOR OPTIONS	34
	INSTALLATION GUIDE	38
03	OTHER PRODUCTS	40
	HOSPITAL DOOR SERIES	40
	SOUND-PROOF DOOR	46
	FIRE SHUTTER DOOR & ROLLER SHUTTERS DOOR	50
	EXPLOSION-PROOF DOOR & EXPLOSION RELIEF DOOR	52
	FIRE WINDOW & EXPLOSION-PROOF WINDOW	54
04	HARDWARE PARTS	56
05	PRODUCTION LINE & PACKAGING	60

COMPANY INFORMATION

Henan Zowor Fire Science and Technology Co., Ltd, founded in 2009, is a rapid expanding manufacturing company in fire door industry. After 10 years development Zowor has become a leading fire doors manufacturer all over China. Our products range from steel fire doors, wooden fire doors, wood interior doors, WPC doors and villa doors. Quality and service has been and also will be our core competitiveness. We are always keeping good cooperation relationship with many high-end real estate builders such as Green Garden and Evergrand and many research institutes such as the Architectural Design and Research Institute of Henan Province. And we have always been enjoying good reputation around our partners domestically and internationally.

Zowor places great emphasis on technical exploration and development. We set up a specialized technical panel with members having more than 8 years of R&D experiences in fire door industry for development of new products and technology. Their commitment enable our company to launch more than 5 patents a year. In October 2019 we were honored as “Model Production Base of Door Systems with Low K-value” of China National Key R&D Plan “Green Buildings and Industrialization of Buildings” in China 13th Five-year planning.



OUR CLIENTS



OUR MARKET





STEEL FIRE DOOR

// DOUBLE FIRE DOOR

- **Certifications:** Certified with UL/NFPA/EN/BS/GB
- **Fire rated time:** 20 mins up to 180mins
- **Double Door customized Max Size:** 9'- 5.7" * 10'-2.2" ft (height)
- Available with handle lock, panic bar and fire-proof window



SF02




Single Rabbet

Single Rabbet

Double Rabbet

DOOR COMPONENTS



DOOR TYPE SHOW




SF04




SF06

DOOR APPLICATION



SF05



SF07



// SINGLE FIRE DOOR

- **Certifications:** Certified with UL/NFPA/EN/BS/GB
- **Fire rated time:** 20 mins up to 180mins
- **Single Door customized Max Size:** 5' * 10' 2.2" ft (height)
- Available with handle lock, panic bar and fire-proof window

Steel fire doors are made of high-strength steel and serve as fire safety facilities in buildings. They possess excellent fire resistance and durability, effectively protecting people's lives and properties.

Additionally, they also offer features such as anti-theft, anti-collision, sound insulation, and thermal insulation.





SF20

EXPLODED VIEW OF DOOR



DOOR TYPE SHOW



Single Rabbet

Single Rabbet

Double Rabbet



SF22

SF23

SF24



SF25

SF26

SF27

DOOR APPLICATION



SF22



SF23



SF24



SF28



SF25



SF26



SF27



SF29




SF30



SF31



SF33



SF32



SF34

// TECHNICAL INTRODUCTION

Zowor fire door meets UL/NFPA/EN/BS/GB standard, complying these criteria as UL 10B, UL10C, NFPA-252,EN-1634-1,BS-476-22. Doors are with UL/EN certificate.UL/NFPA/EN/BS 20 minutes up to 3 hours fire rating. Available with fire proof glazing and top light widely applied to Industrial, Commercial, Chemical, Nuclear and Medical Industries.

FRAME

Various kinds design of frame profiles are available, suitable for different installation environment.

HARDWARE AVAILABLE

UL/Non-UL panic bar, external level trim, door closer, hinge, flush bolt, vision glass, magnetic door holder, coordinator, smoke seal, handle lock, automatic door bottom seal etc.

OPTION

Door and frame surface finish could be customized according to RAL color chart.

CARVING / INLAY OPTIONS


Customized metal/wood trims inlay, profile carving, sometimes change a boring flush door design to a unique and beautiful one.

STEEL DOOR SKIN

16GA(1.5mm),18GA(1.1mm),20GA(0.9mm)
A40 Galvanized Or Cold-rolled Steel Skins
Construction is 1-3/4 " (45mm)Thickness

Hinge, closer, lock and strike plate reinforcements shall be provided.
Hinge reinforcement:10GA(3.5mm)
Closer reinforcement:12GA(2.5mm)
Lock reinforcement:16GA(1.5mm)
Strike plate reinforcement:16GA(1.5mm)

The top, bottom and side closures are fabricated from 16GA(1.5mm) thick channel shaped steel sections welded to the front and back door skins.
Flush top channel:16GA(1.5mm)
Laser-welded side-seamed edge.
Widths up to and including 5 " ft
Heights up to and including 10 ' -2.2 " ft
Available with polystyrene core, honeycomb core or Perlite



TYPICAL STEEL FRAME DESIGN

Double Rabbet



Single Rabbet



Cased Open



Double Egress



Double Rabbet



Typical Wall Construction

Butted



Wire



T



Stud



Sill anchor






Pressure anchor



Typical Sill And Wall Anchors


Sill anchor (loose)

Expansion-Shell Anchor
(Standard)Adjustable Masonry Anchor
(Optional, on request only)

Door frame



MASONRY/STUD CONSTRUCTION FRAME



Wire Anchor


T Anchor

Universal Anchor


Tube Anchor

Jamb Depth	4-3/4 "	5-3/4 "	6-1/4 "	6-3/4 "	7-1/4 "	7-3/4 "	8-1/4 "	8-3/4 "	9-1/4 "	10-1/4 "
Throat Opening	3-3/4 "	4-7/8 "	5-1/4 "	5-3/4 "	6-1/4 "	6-3/4 "	7-1/4 "	7-3/4 "	8-1/4 "	9-1/4 "

DRYWALL FRAME




Frame Profiles




steel fire doors conform or exceed SDI/HMMA industrial standards, fire tested and certified with UL, Intertek/WH from 20Min up to 3hrs fire rating, complying criteria as UBC7-2, ANSI/UL10C UL10B CAN/ULC-S104

OPEN DIRECTION INDICATOR


The direction of opening the door can be based on customer need




Left inside open




Right inside open




Left outside open




Right outside open




Left inside open



Right inside open



Left outside open




Right outside open

EMBOSSED PANELS

Another easy way to make your door look great is with embossed panels. This is a cost-effective metal version of Stile and

Rail wood doors that bring a traditional and elegant look to your door. With up to 8 panels, you have variety of options to find the right look for your aesthetic.



SF40

SF41

SF42



Flush

Vision Lite

Louvered



Two Panel

Four Panel

Six Panel

// DOOR SURFACE TREATMENT

WOOD GRAIN TRANSFER

Wood grain transfer is a process of applying a wood grain pattern onto a surface, typically used for non-wood materials, to create the appearance of real wood.

After the transfer process, the surface will have the appearance of real wood, with the texture and wood grain pattern imprinted onto it, providing a wide range of design possibilities.



SF50



SF51



SF52

COLOR
OPTIONS



4k9058-3



4k9035-5



ps1583



wt01



wt02



wt03



wt04




wt05



wt06



wt07



wt08



wt09



SF53



SF54



SF55

*customized color options, and don't hesitate to contact our sales representatives for more information.

SPRAYING PROCESS COLOR OPTIONS

In addition, we provide customization services to create unique colors based on our customers' specific requirements. Whatever color you need, we can meet your needs and provide personalized color schemes for your products.

RAL 1000	RAL 1013	RAL 1034
RAL 1001	RAL 1014	RAL 1035
RAL 1002	RAL 1015	RAL 1036
RAL 1003	RAL 1016	RAL 1037
Signalfarbe für Wärmeleitung, Vorstoß, Hitzeleitung (DIN 4944)	RAL 1017	RAL 2000
RAL 1004	RAL 1018	RAL 2001
RAL 1005	RAL 1019	RAL 2002
Signalfarbe für Wärmeleitung von Gelenken und Hinterlassenen (DIN 4944) chromatisches Chromgelb	RAL 1020	Signalfarbe für Durchfluss von Stäben (DIN 2403)
RAL 1007		RAL 2003
verwendet für Rettungsgerüste		RAL 2004
RAL 1011	RAL 1021	RAL 2008
RAL 1012	RAL 1023	RAL 2009
RAL 1033	RAL 1024	RAL 2010
RAL 9010	RAL 1027	RAL 2011
RAL 9007	RAL 1028	RAL 2012
RAL 7005	RAL 1032	RAL 2012

RAL 7006	RAL 7031	RAL 8000
RAL 7008	RAL 7032	Kennfarbe für Durchfluss brennbarer Flüssigkeiten (DIN 2403) RAL 8001
RAL 7009	RAL 7033	RAL 8002
RAL 7010	RAL 7034	RAL 8003
RAL 7011	RAL 7035	RAL 8004
RAL 7012	RAL 7036	RAL 8007
RAL 7013	RAL 7037	RAL 8008
RAL 7015	RAL 7038	RAL 8011
RAL 7016	RAL 7039	RAL 8012
RAL 7021	RAL 7040	RAL 8014
RAL 7022	RAL 7042	RAL 8015
RAL 7023	RAL 7043	RAL 8016
RAL 7024	RAL 7044	RAL 8017
RAL 7026	RAL 7045	RAL 8019
RAL 7030	RAL 7046	RAL 8022
RAL 9001	RAL 9016	RAL 8023
RAL 9002	RAL 9017	RAL 8024
RAL 9003	RAL 9018	RAL 8025
RAL 9004	RAL 9021	RAL 8027
RAL 9005	RAL 9022	RAL 8028
RAL 9006	RAL 9023	RAL 8029

RAL 5003	RAL 5000	RAL 6004
RAL 5004	RAL 5001	RAL 6005
RAL 5005	Signalfarbe für Hinweise, Schutzpflicht (DIN 4844) RAL 5002	RAL 6006
RAL 5007	RAL 5025	RAL 6007
RAL 5008	RAL 5026	RAL 6008
RAL 6027	Signalfarbe für Erste Hilfe, Notausgang (DIN 4844) RAL 6002	RAL 6009
RAL 5009	RAL 6003	RAL 6010
RAL 5010	Signalfarbe für (unterrichtendes) Gebot (DIN 4844) RAL 6012	RAL 6011
RAL 5011	RAL 6013	RAL 6028
RAL 5012	RAL 6014	RAL 6029
RAL 5013	auch als Lufthansa Blau bezeichnet RAL 6015	RAL 6031
RAL 5014	RAL 6016	RAL 6032
RAL 5015	Kennfarbe für Durchfluss von Sauerstoff (DIN 2403) RAL 6017	RAL 6033
RAL 5017	Kennfarbe für Durchfluss von Wasser (DIN 2403) RAL 6018	RAL 6034
RAL 5018	RAL 6019	RAL 6035
RAL 5019	RAL 6020	RAL 6036
RAL 5020	RAL 6021	RAL 7000
RAL 5021	RAL 6022	RAL 7001
RAL 5022	RAL 6024	RAL 7002
RAL 5023	RAL 6025	RAL 7003
RAL 5024	RAL 6026	RAL 7004

RAL 2013	RAL 3016	RAL 4006
	RAL 3017	RAL 4007
Kennfarbe für Durchfluss von Dampf (DIN 2403) Signalfarbe für Verbot, Halt, Notaus (DIN 4844) RAL 3000	RAL 3018	RAL 4008
RAL 3001	RAL 3020	RAL 4009
Signalfarbe für Brandbekämpfung (DIN 4844) RAL 3002	RAL 3022	RAL 4010
RAL 3003	RAL 3027	RAL 4011
RAL 3004	RAL 3031	RAL 9011
RAL 3005	RAL 3032	RAL 3014
RAL 3007	RAL 3033	RAL 3015
RAL 3009	RAL 4001	RAL 4004
RAL 3011	RAL 4002	RAL 4005
RAL 3012	RAL 4003	RAL 3013

* Due to variations in monitors, there may be slight color variations in the actual colors. When viewing our color chart on electronic devices, please be aware that colors may be influenced by screen brightness, contrast, and color settings.

// INSTALLATION GUIDE

For proper installation, consult our customer manager for detailed guidance. Here's a summary of the installation process:

A. Pre-Installation:

1. Clear door opening of debris.
2. Verify level and square door frame.
3. Double-check door dimensions for fit.

B. Door Alignment and Positioning:

1. Place door in opening, centering it vertically and horizontally.
2. Use shims if needed for alignment.

C. Fastening the Door:

1. Secure door to frame using suitable screws or anchors.



2. Allow for necessary adjustments.

D. Hinge Installation:

Mark hinge locations on door frame and door.

Install hinges with proper alignment and secure attachment.

E. Lockset Installation:

1. Measure and mark lockset location on the door.
2. Follow manufacturer's instructions to install lockset components.

F. Finishing Touches:

1. Test door operation for smooth movement.
2. Adjust door and hardware as needed.
3. Apply touch-up paint to cover any marks or scratches.

For specific requirements, please contact our customer manager for detailed personalized installation guide.




OTHER PRODUCTS

HOSPITAL DOOR SERIES

Medical doors are equipped with unique features and characteristics to meet the specific needs and requirements of healthcare environments, ensuring safety, hygiene, and convenience.

Hygiene Performance: Medical doors are typically made of easy-to-clean and antimicrobial materials to maintain a sanitary environment. These doors have smooth surfaces that are non-absorbent and easy to disinfect, effectively preventing the spread of bacteria, viruses, and other pathogens.

Fire Protection: Medical doors often have certain fire resistance capabilities, acting as a barrier in case of a fire incident, protecting the safety of personnel and equipment.



DOOR APPLICATION



SF66



SF67

Sound Isolation: Medical doors can provide excellent sound isolation, preventing the transmission of noise and maintaining a quiet and private healthcare environment.

Safety Control: Medical doors are often equipped with safety control systems such as fingerprint recognition, card access control, etc., to restrict access by unauthorized individuals, ensuring the security and confidentiality of medical facilities.

Easy Passage: Medical doors are designed for ease of use and convenient passage, with features such as automatic opening, foot-activated switches, or doors equipped with accessibility features.



SF68



Medical doors play a vital role in healthcare environments, providing secure, hygienic, and convenient access solutions. They can be customized to meet different medical needs and environmental requirements, catering to various applications and scenarios.



SOUND-PROOF DOOR

Soundproof doors are specially designed doors that have the following features and advantages:

Excellent soundproofing performance: They are built with sound-absorbing materials and sealed design to effectively reduce noise transmission and minimize disturbances.

Multilayer structure: Soundproof doors consist of multiple layers of materials such as solid wood, steel plates, and sound insulation fillings, providing superior soundproofing capabilities.



SF80

WOOD SOUND-PROOF DOOR



SF81

SF82

SF83



SF84



SF85



SF86

STEEL SOUND-PROOF DOOR



SF87



SF88



SF89



Strong sealing performance: With small gaps and tight seals, they prevent sound from passing through the door, enhancing the soundproofing effectiveness.

High strength and security: Soundproof doors are made of sturdy materials and designed with durable structures, ensuring both strength and security to protect the premises.

Versatile appearance and styles: They come in a variety of designs and styles to suit different interior designs and decorations.



SF90

FIRE SHUTTER DOOR & ROLLER SHUTTERS DOOR

FIRE SHUTTER DOOR



SD01



SD02

ROLLER SHUTTERS DOOR



SD03



SD04

EXPLOSION-PROOF DOOR & EXPLOSION RELIEF DOOR

EXPLOSION-PROOF DOOR



EXPLOSION RELIEF DOOR



FIRE WINDOW & EXPLOSION-PROOF WINDOW

FIRE WINDOW



SD09



SD10

EXPLOSION-PROOF WINDOW

Our bulletproof windows are made with high-quality special materials and advanced manufacturing techniques, providing excellent resistance to impact and explosions.

We offer a variety of specifications and models of bulletproof windows to meet the diverse needs of our customers. Whether it is for government institutions, military facilities, or commercial buildings, we can provide you with high-quality bulletproof windows to protect the safety of your personnel and property.



SD11



SD12



HARDWARE PARTS



Handle-1



Handle-2



Handle-3



Handle-4



Smart Lock-1



Smart Lock-2



Smart Lock-3



Smart Lock-4



Mortise Lock-1



Mortise Lock-2



Cylinder-1



Cylinder-2



Closer-1



Closer-2



Closer-3



Cylindrical lock-1



Cylindrical lock-2



Mortise Lock-1



Mortise Lock-2



Closer-4



Lever trim-1



Lever trim-2



Lever trim-3



Mortise lock-3



Viewer



Butt Hinge-1



Spring Hinge-2



Concealed hinge



Bottom seal



Magnetic door holder



Pull & push



Push Bar-1



Coordinator-1



Coordinator-2



Flush bolt

HARDWARE PARTS



Push Bar-2



Push Bar-3



Push Bar-4




Push Bar-5



Push Bar-6




Threshold Plate-RP28



Panic bolt (by others)



Threshold Plate Seal-RP117Si



Panic bolt (by others)



Brush Strip Seal-RP129



Perimeter Seal-RP70Si



half-round door stop



Water Drop Seal-RP700



anti-kick plate

PRODUCTION LINE & PACKAGING

PRODUCTION LINE

We have two production bases in Shanghai and Zhejiang province occupies an area of 23000 square meter.

Integrated with Independent R&D team,Germany advanced technology and top grade numerical automatic production facilities,

such as automatic sheet metal break machine, CNC machine, painting & coating line.



Factory has passed ISO9001:2015 quality management systems.

Our main product:Steel fire door,Steel fidoor,Wooden fire rated door & window,Shutter ect.



PACKAGING

Moisture-proof, dust-proof and shock-proof package meets requirements of long-distance transport and open storage.



Packing on a pallet



Load the door into the container with a forklift



Packed and packed into containers (Length: 12 meters)



Package for the products: Plastic foam+Bubble wrap +Strong carton(optional).

